

Document PAS022  
Revision A1 – 6/15/07

---

---

**PAS 9418/AO**  
**ENGINEERING SPECIFICATION**

---

---

**16 CHANNEL**  
**HIGH POWER AMPLIFIER**  
**VME ANALOG OUTPUT CARD**  
**Revision A (6/15/07)**

Additional copies of this manual or other Precision Analog Systems (PAS) literature may be obtained from:

Precision Analog Systems Co.  
1021 SW 75<sup>th</sup> Avenue  
Plantation, Florida 33317  
Phone: (954) 587-0668  
E-mail: [inquiry@precisionanalog.com](mailto:inquiry@precisionanalog.com)

The information in this document is subject to change without notice.

PAS makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Although extensive editing and reviews are performed before release, PAS assumes no responsibility for any errors that may exist in this document. No commitment is made to update or keep current the information contained in this document.

PAS does not assume any liability arising out of the application or use of any product or circuit described herein, nor is any license conveyed under any patent rights or any rights of others.

PAS assumes no responsibility resulting from omissions or errors in this manual, or from the use of information contained herein.

PAS reserves the right to make any changes, without notice, to this product to improve reliability, performance, function or design.

All rights reserved.

# 16 Channel High Power Amplifier VME Analog Output Card

## TABLE OF CONTENTS

Section	Title	Page
I	<b>INTRODUCTION</b>	5
	General Description	5
	Card Features	5
II	<b>SPECIFICATIONS</b>	6
	Electrical Specifications	6
	Environmental Specifications	6
	Physical Specifications	6
	Jumpers and Indicators	7
	Connector Definitions	8
III	<b>CIRCUIT DESCRIPTION</b>	10
IV	<b>CALIBRATION PROCEDURE</b>	11
	Offset Adjustment	11
	Gain Adjustment	11

# 16 Channel High Power Amplifier VME Analog Output Card

## LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
1	Pluggable Jumper Definitions	7
2	6 Position Molex Header	8
3	DB37 Connectors (P3 and P4)	9
4	Gain and Offset Potentiometers	11

# I. INTRODUCTION

## GENERAL DESCRIPTION

The PAS 9418/AO provides sixteen high power amplifier circuits on a 6U format card. This amplifier is pin compatible with the PAS 9716/AO, 16-channel, 16-bit Analog Output card. By using the combination of these two cards, a VME based analog output system can be constructed that will supply up to +/- 160 volts and up to 50 mAmps of output current.

External power supplies are required to power the amplifiers, and a front panel connector is provided for wiring to these supplies. The front panel also provides two DB37 connectors. One terminates the input signals and the other provides the amplified output signals. Both of these connectors have the same pin out as the PAS 9716 Analog Output card.

The maximum current and voltage that can be delivered by the amplifiers is primarily determined by the amplifier's power dissipation. This is dependent on supply voltage and load impedance. Custom versions of this board can be provided with gain and output drive tailored to the application.

This version of the card uses PA241DW amplifiers and previous versions used the now discontinued PA42. See Section III for more information.

### Card Features: PAS 9418/AO

Number of Channels	16
Output Voltage	+/- 60 Volts (typ.), +/- 85 Volts (max.) +/- 160 Volt Outputs available with component changes
Output Current	+/- 50 mAmps (typ.)
Input Voltage	+/- 10 Volts (typ.), +/- 35 Volts (max.)
Gain	3 or 6, jumper selectable
External Power Supply	+/-50 VDC (min.), +/- 75 VDC (typ.), +/- 100 VDC (max.) +/- 175 VDC available with component changes
Slew Rate	10 Volts / uSec. (typ.)
Full Power Bandwidth	25 KHz (typ) @ V out 120 V pk-pk
Status LEDs	2 front panel LEDs are driven by the PAS 9716 Digital Outs
Size	6U format, 160 mm x 233 mm
Input / Output Connectors	2 ea. DB 37 female
Power Supply Connector	6 position shrouded header (Molex)

## II. SPECIFICATIONS

### Electrical Specifications

Number of Channels	16 Analog Outputs
Output Voltage	+/- 60 Volts (typ.) +/- 85 Volts (max.) +/- 160 Volt outputs with component change
Output Current	+/- 40 mAmps (min.), +/- 50 mAmps (typ.)
Input Voltage	+/- 10 Volts (typ.), +/- 35 Volts (max.)
Gain	3 or 6, jumper selectable
Zero Error	+/- 5 mV, (adjustable to zero)
Gain Error	+/- 0.1 % FS, (adjustable to zero)
Slew Rate	10 V / uSec (typ.)
Full Power Bandwidth	25 KHz (typ.) V out = 120 V pk-pk, 1.5 K ohm load
Output Voltage Swing	+/- Vs-12 Volts (min.), +/- Vs-10 Volts (typ.) @ I out = 40 mAmps
Card Power Requirements (VME Bus)	+/- 12 Volts @ 30 mAmps (typ.)
(External Power Supplies)	+/- 50 VDC to +/- 100 VDC +/- 175VDC with component changes @ +/- 65 mAmp (No Load) @ +/- 900 mAmp (Full Load)

### Environmental Specifications

Operating Temperature Range	0 to 55 degrees C.
Storage Temperature Range	-20 to 85 degrees C.
Junction Temperature	150 degrees C. (max.)
Thermal Resistance (junction to air)	55 degrees C. / Watt (typ.)
Relative Humidity Range	20% to 80%, non-condensing

### Physical Specifications

Dimensions	Form factor: Double (160 mm x 233 mm)
Weight	12 oz. (typ)
Connectors	2 ea. DB37 female, (Analog Input and Output connectors) 1 ea. 6 pin shrouded header (External power connector) Mating connector, Molex P/N 50-57-9406

## Jumpers and Indicators

The 9418/AO card contains 16 Pluggable jumpers and two LED indicators. All of the jumpers have three pins, and provide two possible jumper locations. Pin 1 of each jumper strip is defined with a square pad in the PC board layout.

These 16 jumpers are used to set each channels gain to either three or six. Gain of three is selected by installing the jumpers from pin 1 to 2. This is the left position for the jumpers.

Gain of six is selected by installing the jumpers from pin 2 to 3. This is the right position for the jumpers.

**TABLE 1**  
**PLUGGABLE JUMPER DEFINITIONS**

<b><u>Jumper #</u></b>	<b><u>Function</u></b>
J1	Gain CH 0
J2	Gain CH 1
J3	Gain CH 2
J4	Gain CH 3
J5	Gain CH 4
J6	Gain CH 5
J7	Gain CH 6
J8	Gain CH 7
J9	Gain CH 8
J10	Gain CH 9
J11	Gain CH 10
J12	Gain CH 11
J13	Gain CH 12
J14	Gain CH 13
J15	Gain CH 14
J16	Gain CH 15

Two LEDs are provided at the front panel to indicate the board's status. These LEDs are steered by the DO1 and DO2 signals from the 9716 Analog Output card. If the amplifier is not wired directly to the AO card, then the LEDs will be driven by the signals that are wired to pins 1 and 2 of P3.

## Connector Definitions

Two 96 position DIN connectors are installed on the back plane end of the board and connect to the VME bus to bring in +/- 12 Volts. This voltage is used for the offset adjustment of the amplifier circuits. The board also jumpers through the bus grant and interrupt acknowledge signals using these connectors.

Two DB37 female connectors are installed through the board's front panel to provide access to the sixteen analog output channels and the two digital outputs. The pin out of these connectors is defined on the following page.

A six-position Molex header is provided at the front panel, and located between the two DB37 connectors. This connector is used to bring in external power to the amplifiers. The mating connector to this header is Molex P/N 50-57-9406, and the crimp on pin P/Ns are 16-02-1114 or 16-02-1125.

The pin out of this connector is defined below.

**TABLE 2**

**6 Position Molex Header**

1	Positive Power Supply
2	Power Supply Ground
3	Negative Power Supply
4	N/C
5	N/C
6	N/C



**TABLE 3**

**DB37 Connectors (P3 and P4)**

AGND	37	19	AGND
AGND	36	18	CH1H
AGND	35	17	CH3H
AGND	34	16	CH5H
AGND	33	15	CH7H
AGND	32	14	CH9H
AGND	31	13	CH11H
AGND	30	12	CH13H
AGND	29	11	CH15H
AGND	28	10	CH0H
AGND	27	9	CH2H
AGND	26	8	CH4H
AGND	25	7	CH6H
AGND	24	6	CH8H
AGND	23	5	CH10H
AGND	22	4	CH12H
AGND	21	3	CH14H
AGND	20	2	DO1
		1	DO2

P3 is the input connector and P4 is the output connector. The same signal names are used in the input and output connectors. Example; CH0H input is P3 pin 10, and CH0H output is P4 pin 10.

### III. CIRCUIT DESCRIPTION

The PAS 9418/AO card contains 16 high power amplifier circuits. Cards can be configured to either provide a gain of three or gain of six. In either case, the output current and voltage range will be increased significantly when compared with a standard analog output card.

All of the amplifier circuits have gain and offset adjustments. A calibration procedure is provided on the page 11, and describes how to make these adjustments.

The amplifiers used on this card are high voltage monolithic MOSFET operational amplifiers. They deliver performance features previously only found in hybrid designs, while increasing reliability. The amplifier part number is PA241DW, and is built by Apex Microtechnology Corporation.

The PA241DW is packaged in Apex's hermetic SIP10 package. This package has a typical thermal resistance of 55° C per Watt from junction to air, and the device has a maximum junction temperature of 150° C.

When the amplifier card is configured to drive 60 Volts at 50 mAmps into a resistive load with  $\pm$  Volt power supplies, the maximum power in the amplifier will be 1.17 Watts. In this example, the load resistance is 1.2 K ohms, and the maximum power dissipation in the amplifier occurs at half of the power supply voltage. As the output voltage increases from this point, the voltage across the amplifier decreases, and as the output voltage decreases, the current through the amplifier and the load decreases. When the amplifier is driving this load to 60 Volts, it is delivering 3 Watts of power to the load, and the amplifier is dissipating 750 mWatts.

This board was originally designed with the PA42 amplifier. The PA241 replaced the PA42 and the compensation components around the amplifier were adjusted for the PA241. The performance of the PA241 is very similar to that of the PA42 and this version of the PAS 9418/AO should perform just like the previous versions. If any performance variations are observed, please contact Precision Analog Systems.

## VI. CALIBRATION PROCEDURE

Configure all sixteen jumpers on the PAS 9418/AO card to position 2 to 3. This configures all channels on the card for the gain of 6. Install the card in a VME chassis, and connect the external power supplies. Allow the card to stabilize for approximately 15 minutes.

### Offset Adjustment

Connect all of the input signals to ground, either using a shorting connector or by connecting the card to a PAS 9716/AO card and driving the outputs to zero Volts. Observe the individual output channels with a Voltmeter and adjust the zero pot on each channel for zero Volts. The offset adjustment pots are defined in the table below.

### Gain Adjustment

Drive all of the input signals to 10.00 Volts, and adjust all of the gain pots so that all of the outputs are at 60.00 Volts. The gain adjustment pots are defined in the table below.

**TABLE 4**

**Gain and Offset Potentiometers**

CH #	Offset Pot	Gain Pot
0	R4	R10
1	R16	R22
2	R28	R34
3	R40	R46
4	R52	R58
5	R64	R70
6	R76	R82
7	R88	R94
8	R100	R106
9	R112	R118
10	R124	R130
11	R136	R142
12	R148	R154
13	R160	R166
14	R172	R178
15	R184	R190